



We will come to you  
anywhere in the country  
for a free demonstration.

- ※Please contact us regarding Hokkaido, Okinawa,  
and remote islands.
- ※Rentals are also available.

Warranty and after-sales service for the FEB-HP series will be handled by Faisca Co., Ltd.



【本社】  
愛知県豊橋市西松山町1 2 3 番地 3  
TEL:0532-39-8631  
FAX:0532-39-8632  
E-mail:feb\_faisca@faisca.co.jp  
URL:https://faisca.co.jp

0120-378-631



【熊本営業所】  
熊本県熊本市東区長嶺東 6 丁目 3 0 - 6  
TEL:096-292-7667

2026年5月改訂

FEB-HP

スポット



# Environmental improvement for factory, warehouse, etc.

And for Event venues, gymnasiums, and vaccination sites, etc.  
**Preventing heatstroke** in facilities ranging from small to large spaces

- Compact and lightweight
- A strong wind of 10 m/s
- For use in small spaces or by small groups
- It can also be used by connecting up to 2 ducts.



FEB-HP SPOT TypeJ			
Power supply	3 φ 3W 200V		1 φ 2W 200V
External dimensions	W1050 × D1050 × H1550 (mm)		
Weight	125kg		
Cooling capacity	5.0kw		
Heating capacity	5.6kw		
Air volume	Strong 16	Medium 15	Weak 12 m <sup>3</sup> /min
Electrical characteristics	Operating current	Cooling 4.3A Heating 4.8A	Cooling 7.5A Heating 8.3A
	Power consumption	Cooling 1.38 kw Heating 1.55kw	
	Power factor	93%	
	Max current	10.1A	17.8A

- With a powerful wind speed of 11 m/s, it can reach up to 8 meters away, making it suitable for use in factories, warehouses, event venues, indoor workshops, gymnasiums, etc.
- It can also be used by connecting up to 4 ducts.



FEB-HP SPOT TypeR			
Power supply	3 φ 3W 200V		
External dimensions	W1640 × D1060 × H1660 (mm)		
Weight	200kg		
Cooling capacity	12.5kw		
Heating capacity	14.0kw		
Air volume	Strong 39	Medium 33	Weak 28 m <sup>3</sup> /min
Electrical characteristics	Operating current	Cooling 13.6A Heating 12.0A	
	Power consumption	Cooling 4.45kw Heating 3.90kw	
	Power factor	Cooling 94.5% Heating 93.8%	
	Max current	25.3A	

- Suitable for large spaces
- High airflow
- Delivers cool air at 11 m/s up to approximately 10 meters away

- It can also be used by connecting up to 8 ducts.



FEB-HP SPOT TypeM			
Power supply	3 φ 3W 200V		
External dimensions	W670 × D1520 × H1740 (mm)		
Weight	295kg		
Cooling capacity	20.0kw		
Heating capacity	22.4kw		
Air volume	Strong 68	Medium 58	Weak 46 m <sup>3</sup> /min
Electrical characteristics	Operating current	Cooling 20.5A Heating 19.0A	
	Power consumption	Cooling 6.99 kw Heating 6.43kw	
	Power factor	93%	
	Max current	26.5A	

• Product specifications are subject to change without notice.

- Both air conditioning and heating are available
- Equipped with casters for easy movement; ready to use with a power source.
- With a powerful wind speed of 10m/s, it can reach up to 5 meters away,
- By connecting the duct, you can direct the airflow to your desired location.
- You can choose from 4 types.
- High-performance air filter installed



FEB-HP SPT TypeS			
Power supply	3 φ 3W 200V		1 φ 2W 200V
External dimensions	W1250 × D1050 × H1550 (mm)		
External dimensions (small)	W1200 × D800 × H1380 (mm)		
Weight	140kg		
Cooling capacity	7.1kw		
Heating capacity	8.0kw		
Air volume	Strong 21	Medium 19	Weak 15 m <sup>3</sup> /min
Electrical characteristics	Operating current	Cooling 7.1A Heating 7.3A	Cooling 12.7A Heating 12.1A
	Power consumption	Cooling 2.32kw Heating 2.36kw	
	Power factor	94%	
	Max current	10.5A	17.3A

Temperature can be set using a wired remote control.



- A variety of functions
- Japanese only
- Cooling 18°C ~ 30°C
- Heating 16°C ~ 30°C
- Dehumidification 18°C ~ 30°C
- ※ The set temperature range varies

- Options
- You can change the wind direction and direct the wind to your desired location.



Installation Examples